

European leader for ozone water treatment



## Ozonator EX 100

- No maintenance
- Performances increase
- Easy use
- Latest electronic
- Air or water cooling
- Absorption and filtering of ambient air

**A quality reference**  
for an always purest water  
without any consumables

European leader for ozone water treatment

OZONEX adapts its manufacturing according to pools and volumes to treat.

## EX 100

### 1 Polycarbonate box

Width : 280 mm – Height: 380 mm  
Depth: 140 mm  
Weight : 4,0 Kg – Volume : 0,006 m<sup>3</sup>  
Metallic Faraday cage

### 1 Front face with identification

1 power up led ( green )  
1 ozone production led (blue)  
1 switch

### 1 Electronic card

1 THT card- High Voltage  
Temporisation  
1 fuse / 1 ampere

### Assembly accessories

1 Stainless steel double check valve (316.L)  
with Viton joints and crystal ball  
1 PTFE Ozone tube - diameter 6x4

### 1 Electrical connection

220 volts / 50 HZ  
Power Cable (3G1.5)

### 1 Ozone generator

Production ( + - ) 2 Grs / hour  
For maximum flow of  
25 m<sup>3</sup> water / hour  
Air flow from 0 to 80 liters / hour

### Various

1 air filter  
1 solenoid valve (on / off – ozone)

### Materials driving ozone

PTFE for tubes  
PVDF for solenoid valve and fittings  
VITON for joints  
Stainless steel 316L for double check valve  
1 power supply 220V / 50HZ  
(110V / 60HZ if needed )  
Electrical consumption : 30 watts / hour