

European leader for ozone water treatment



Ozonator EX 200

- Cost effective
- Ecological
- Natural

A quality reference
for an always purest water
without any consumables.

European leader for ozone water treatment

OZONEX adapts its manufacturing according to pools and volumes to treat.

EX 200

1 Metal box

Width: 300 mm - Height : 400 mm
Depth : 200 mm
Weight : 12 Kg

1 Front face with identification

2 power up leds (green)
2 ozone production leds (blue)
1 switch
1 flowmeter

2 Electronic cards

2 THT cards- High Voltage
Temporisation
2 fuses / 1 ampere

Assembly accessories

1 Stainless steel double check valve (316.L)
with Viton joints and crystal ball
1 PTFE Ozone tube - diameter 6x4

1 Electrical connection

220 volts / 50 HZ
Power Cable (3G1.5)

2 Ozone generators

Production (+ -) 3 Grs / hour
For maximum flow of 50 m³ water / hour
Air flow from 0 to 80 liters / hour
1 ozone exit

Various

1 air filter
1 solenoid valve (on / off - ozone)

Materials driving ozone

PTFE for tubes
PVDF for solenoid valve and fittings
VITON for joints
Stainless steel 316L for double check valve
1 power supply 220V / 50HZ
(110V / 60HZ if needed)
Electrical consumption : 60 watts / hour