

European leader for ozone water treatment



Ozonator EX 200 SP

- Cost effective
- Ecological
- Natural

A quality reference
for an always purest water
without any consumables.

European leader for ozone water treatment

OZONEX adapts its manufacturing according to pools and volumes to treat.

EX 200 SP

1 Metal box

Width : 300 mm - Height : 400 mm
Depth : 200 mm
Weight : 12 Kg

1 Front face with identification

2 power up leds (green)
2 ozone production leds (blue)
2 switches
2 flowmeters

2 Electronic cards

2 THT cards- High Voltage
Temporisation
2 fuses / 1 ampere

Assembly accessories

2 Stainless steel double check valves (316.L)
with Viton joints and crystal ball
2 PTFE Ozone tubes - diameter 6x4

1 Electrical connection

220 volts / 50 HZ
Power Cable (3G1.5)

2 ozone generators

Production (+ -) 3 Grs / hour
For maximum flow of 2x25 m³ water / hour
Air flow from 0 to 80 liters / hour
2 ozone exits

Various

2 air filters
2 solenoid valves (on / off - ozone)

Materials driving ozone

PTFE for tubes
PVDF for solenoid valve and fittings
VITON for joints
Stainless steel 316L for double check valve
1 power supply 220V / 50HZ
(110V / 60HZ if needed)
Electrical consumption : 60 watts / hour