

European leader for ozone water treatment



Ozonator

OZO 100

- No maintenance
- Performances increase
- Easy use
- Latest electronic
- Air or water cooling
- Absorption and filtering of ambient air

A quality reference
for an always purest water
without any consumables

European leader for ozone water treatment

OZONEX adapts its manufacturing according to pools and volumes to treat.

OZO 100

1 Polycarbonate box

Width : 370 mm – Height: 415 mm
Depth : 100 mm
Weight : 5,5 Kg

1 Front face with identification

1 power up led (green)
1 ozone production led (blue)
1 ozone control led (red)
1 switch
1 flowmeter

1 Electronic card

1 THT card- High Voltage
Temporisation
1 fuse / 1 ampere

Assembly accessories

1 Stainless steel double check valve (316.L)
with Viton joints and crystal ball
1 PTFE Ozone tube - diameter 6x4

1 Electrical connection

220 volts / 50 HZ
Power Cable (3G1.5)

1 Ozone ceramic generator

Production (+ -) 5 Grs / hour
For maximum flow of
25 m³ water / hour
Air flow from 0 to 80 liters / hour
1 ozone exit

Various

1 air filter
1 solenoid valve (on / off – ozone)

Materials driving ozone

PTFE for tubes
PVDF for solenoid valve and fittings
VITON for joints
Stainless steel 316L for double check valve
1 power supply 220V / 50HZ
(110V / 60HZ if needed)
Electrical consumption : 75 watts / hour