



Swimming pools & Spas

European leader for ozone water treatment



Ozonator OZO SPAS

- Cost effective
- Ecological
- Natural

A quality reference
for an always purest water
without any consumables.

European leader for ozone water treatment

OZONEX adapts its manufacturing according to pools and volumes to treat.

OZO SPAS

1 Polycarbonate box

Width : 140 mm - Height: 380 mm
Depth : 120 mm
Weight: 5 Kg

1 Front face with identification

1 power up led (green)
1 ozone production led (blue)
1 switch

1 Electronique card

1 THT card- High Voltage
Temporisation
1 fuse / 1 ampere

Assembly accessories

1 Stainless steel double check valve (316.L)
with Viton joints and crystal ball
1 PTFE Ozone tube - diameter 6x4

1 Electrical Connection

220 volts / 50 HZ
Power Cable (3G1.5)

1 Ozone generator

Production (+ -) 2 Grs / hour
For a maximum flow of
25 m³ water / hour
Air flow from 0 to 30 liters / hour
1 ozone exit

Various

1 air filter
1 solenoid valve (on / off - ozone)

Materials driving ozone

PTFE for tubes
PVDF for solenoid valve and fittings
VITON for joints
Stainless steel 316L for double check valve
1 power supply 220V / 50HZ
(110V / 60HZ if needed)
Electrical consumption : 30 watts / h